


Rigid Conduit Bodies with Cover and Gasket

Threaded LR Type



E195124

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Features

- Threaded LR type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket - Neoprene rubber

Standard Finish

- Powder coat


Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	A	B	C
			Max. Number	Max. Size						
LR1CG	21241	1/2"	1	6 AWG	10	100	36	4.295	1.37	2.03
LR2CG	21251	3/4"	2	6 AWG	10	50	28	5.09	1.625	2.33
LR3CG	21261	1"	3	6 AWG	5	25	17	5.915	1.90	2.65
LR4CG	21271	1-1/4"	3	2 AWG	2	10	15	7.894	2.77	3.385
LR5CG	21281	1-1/2"	3	2 AWG	2	10	18	7.894	2.77	3.385
LR6CG	21291	2"	3	2/0 AWG	1	5	14	10.134	3.335	3.81
LR7CG	21301	2-1/2"	3	4/0 AWG	---	1	7	13	4.063	5.709
LR8CG	21311	3"	3	250 MCM	---	1	7	12.75	4.682	5.506
LR9CG	21321	3-1/2"	3	350 MCM	---	1	10	15.50	5.452	6.171
LR10CG	21331	4"	4	350 MCM	---	1	10	15.50	5.452	6.171

Threaded T Type



E195124

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Features

- Threaded T type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket - Neoprene rubber

Standard Finish

- Powder coat

Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	A	B	C
			Max. Number	Max. Size						
T1CG	21731	1/2"	1	6 AWG	10	100	38	4.72	1.37	1.33
T2CG	21741	3/4"	2	6 AWG	10	50	30	5.57	1.625	1.54
T3CG	21751	1"	3	6 AWG	5	25	20	6.46	1.90	1.74
T4CG	21761	1-1/4"	3	2 AWG	2	10	19	8.528	2.77	2.49
T5CG	21771	1-1/2"	3	2 AWG	2	10	21	8.528	2.77	2.49
T6CG	21781	2"	3	2/0 AWG	---	5	10	10.831	3.335	3.10
T7CG	21791	2-1/2"	3	4/0 AWG	---	1	4	13.50	4.06	5.825
T8CG	21801	3"	3	250 MCM	---	1	5	13.50	4.685	5.825
T9CG	21811	3-1/2"	3	350 MCM	---	1	12	15.937	5.45	7.06
T10CG	21821	4"	4	350 MCM	---	1	9	15.937	5.45	7.06