Featherweight Plus G31H

DESCRIPTION

- · Industrial protective glove.
- Unsupported unflocked natural rubber glove.
- 4 sizes available: 6.5, 7.5, 8.5 and 9.5.
- Trade unit :12 pairs, 144 pairs in a transit case.

CHARACTERISTICS

- · Natural rubber glove, beaded cuff.
- Raised diamond grip finish on palm and fingers for good dry grip.
- · Low modulus for minimal hand fatigue.
- · Length: approximately 320 mm.
- Glove thickness (double wall): approximately 0,70 mm.
- 21CFR (USA) and European Directive compliant for food contact.

PERFORMANCES

- · Good tear resistance.
- · Strong yet sensitive formulation.
- · Tear resistant beaded cuff for easy donning.
- Excellent flexibility and comfort offering a good dexterity.
- In compliance with the standards EN420 (General requirements), EN388 (Mechanical Hazards), EN374 (Chemical and Micro-organisms Hazards) and EN421 (Radioactive Contamination) by the BSI.
- Manufactured under EC quality assurance system carried out by the BSI.

APPLICATIONS

 Ideal for use in laboratories, electronic applications and particulate sensitive areas.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21rst, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests, and manufactured under a CE quality assurance system carried out by a notified body.





EN 388 Mechanical hazards



EN 374 Chemical hazards



EN 374 Micro-organism hazards



EN 421
Radioactive contamination

	$\hat{\mathbf{i}}$
EN420	

EN 420

5 Dexterity

EN 388

2 Abrasion

0 Cut 1 Tear

0 Puncture

EN 374

2 A - Methanol

6 K - Caustic soda solution 40 %

2 L - Sulfuric acid 96 %

Order codes

 Sizes
 6.5 (S)
 7.5 (M)
 8.5 (L)
 9.5 (XL)

 Featherweight Plus G31H
 01630
 01631
 01632
 01633



