

Pigtail Sockets

60/600V



Features

- Right-handed thread
- Left-handed thread
- #14 stranded
- Brass shell contact

Applications

- Ideal for all temporary lighting applications
- Suitable for indoor and outdoor use

Standard Material

- Rubber

Catalog Number	UPC	Size	Left/Right Handed	Unit Carton	Ship Case	Weight/Case	Wire Size
T124	33517	6" Long	Right	25	250	26	14 GA
T124L	85697	6" Long	Left	25	250	26	14 GA

Highbay Worklight

400 Watt



**UL and cUL Listed
for Damp locations**



Meets EISA 2007 for energy efficiency.
Meets NEC 2005 and 2008 requirements.

Catalog Number	UPC	Size	Ship Case	Weight Case
17400HB	86898	3/4"	1	24
17400CG*	86901	---	6	17

* Safety cage only

Features

- Fully assembled to save time and labor costs
- Multi-tap ballast: 120V, 208V, 240V, 277V (Factory wired 120V)
- 400W, clear MH pulse start lamp included
- Corrosion resistant welded steel safety cage included
- Replacement cages can also be purchased separately
- Two .75" knockouts for conduit access for multiple HID fixtures on back
- Easy carry handle
- Type "O" spring loaded pink porcelain screw shell socket
- Heavy duty corrosion resistant welded steel safety cage included (can also be purchased separately #17400CG)
- 3 ft. power cord #18/3 SSJTOW with NEMA 5-15120V, 15 amp plug
- Vented ballast housing to reduce temperature & overheating
- Steel housing, white powder coat finish
- 400W MH Pulse Start Type "O" Lamp included (Use Topaz MP400/BU/PS-37 replacement bulb)
- Open/Close bottom guard 10" opening for easy re-lamping

Applications

- Meets OSHA requirements for minimum illumination of work areas when properly installed